


HSS DRILL BIT

HSS-CO COBALT 5%

EFFICIENT



Ø Max 12.7

Features




- Fully ground drill bit 5% cobalt HSS-E.
- 135° tip angle.
- Split point.
- Flute type N.
- Diameter tolerance h8

Benefits

- Starting precision.
- The cobalt content makes the bit harder and heightens temperature resistance, for work with hard metals such as stainless steel.

Applications

- Unalloyed and alloyed steels (up to 1200N/mm²), stainless steel, cast iron.



DIN 338

Ø	Ref.	Gencod	Qt.
Short Serie			
2	700YD02	4013769434685	10
2,5	700YD02,5	4013769434692	10
3	700YD03	4013769434319	10
3,2	700YD03,2	4013769434708	10
3,5	700YD03,5	4013769434715	10
4	700YD04	4013769434326	10
4,2	700YD04,2	4013769439543	10
4,5	700YD04,5	4013769434722	10
4,8	700YD04,8	4013769434739	10
5	700YD05	4013769434333	10
5,5	700YD05,5	4013769434746	10
6	700YD06	4013769434340	10
7	700YD07	4013769434753	10
8	700YD08	4013769434357	10
8,5	700YD08,5	4013769434760	10
9	700YD09	4013769434777	10
10	700YD10	4013769434784	10
11	700YD11	4013769434791	5
12	700YD12	4013769434807	5

